



Features:

- **USB spec. 2.0 full-speed compatible**
- **Noise cancelling microphone**
With highest voice recognition industry rating
- **Pro-Flex wire microphone boom**
Allows for perfect placement of microphone
- **40mm speakers with CD quality sound**
- **Comfortable foam ear cushions**
Reversible for left or right side usage
- **Microphone windsock**
For minimal breath popping
- **In-line Digital Volume/Mute Controls**
- **Stainless steel adjustable head band**
Folds flat for storage
- **Extra long 8 foot shield cable**



Parameter	Value
Operation	
Power	USB
Microphone Input	1 Channel
Audio Output	2 Channel stereo
Microphone	
Noise Cancellation	5.dB/octave
Frequency Range	100-10,000 Hz
Electrical Signal-to-Noise Ratio	>60 dB
Sensitivity at 1 kHz (0 dB = 1 V/Pa)	-44 dB
Current Consumption	<0.5 mA
A/D Conversion Resolution	16 bit
THD + N	-76 dB
Speakers	
Frequency Range	50-20,000 Hz
Coil Resistance	32 ohm
Sound Output from 1 kHz 1mW	114 dB
Input (0 dB = 20 µPa)	
Maximum Input Power	40 mW
D/A Conversion Resolution	16 bit
THD + N	-71 dB



USB 2.0 Compatible



Proprietary Mic Design



Digital Volume/Mute Control